

Compact 5" - Only 6'6" Long

Compact 6" and 5/6 Combo - Only 8'6" Long

SAVING MORE THAN SPACE

Fits in a half-ton 8' pickup bed or van. Eliminates the need for a $\frac{3}{4}$ or 1 ton vehicle, extended van, or trailer.

Light weight reduces transportation costs.

Produces the same high quality and accurate gutters as full sized machines.

Backed by the best service in the industry



Warranty:
3 Year Parts & Labor
1 Year Electrical

Ph: 866-522-1696 Fax: 800-295-2702

www.senox.com

Specifications |

Dimensions

Length - 78" (5"), 102" (6", 5/6 Combo)

Height - 48" Width - 24"

Weight

5" - 722 lbs, 6" 877 lbs, 5/6 Combo 884 lbs with spin coil cradle

Drive

Powered polyurethane drive rollers via chains and sprockets

Speed

Approximately 35-40 feet per minute

Controls

Push button entry and exit end controls with "jog" feature, dongle

Material Feed

Must be fed from top of machine with cradle or spool

Recommended Materials

11 ⁷/₈" &15" wide

Aluminum 0.027/.032 Galvalume 26 ga. Copper 16 oz. 3/4 hard

Spin Coil Cradle
Full Coil Cradle
Front Pull Guillotine
Standard Run Out Stand
Deluxe Run Out Stand
Turnstile Upright
Spool
Machine Stand
Transfer Bars, Set of 2

Options













POLYURETHANE DRIVE TRAIN

- Eliminates the need to load coil prior to transportation (less material waste)
- Eliminates slippage from cold weather and condensation

.002 HARD CHROME PLATED STEEL FORMING ROLLERS

- · Rollforms all standard metals with minimal or no adjustment
- Free-floating forming rollers produce less pressure and allow for more product uniformity

ELECTRICAL AND CONTROL SYSTEM

- Push button control safety wiring
- Entrance and exit control selector switch jog run
- $3/_4$ HP, 110 Volt, Single Phase Motor, 13.6 Ampere

STRUCTURAL STEEL FRAME

Welded steel frame



