



Full Size 6" Reverse Bead Half Round

Backed by the best service in the industry



Warranty:
3 Year Parts & Labor
1 Year Electrical

Ph: 866-522-1696 Fax: 800-295-2702 www.senox.com

Specifications |

Dimensions

Length -162"

Height - 48"

Width - 24"

Weight

Approximately 1,300 lbs

Drive

Powered polyurethane drive rollers via chains and sprockets

Speed

Approximately 35 feet per minute

Controls

Push button entry and exit end controls with "jog" feature, dongle

Recommended Materials

11.875" wide

Aluminum .027/.032 Galvalume 26 ga.

Copper 16 oz. 3/4 hard

Spin Coil

Full Coil Cradle

Turnstile Upright

Spool

Front Pull Guillotine

Standard Run Out Stand

Deluxe Run Out Stand

Machine Stand

Transfer Bars, Set of 2

Options













POLYURETHANE DRIVE TRAIN

- Eliminates the need to load coil prior to transportation (less material waste)
- Eliminates slippage from cold weather and condensation

.002 HARD CHROME PLATED STEEL FORMING ROLLERS

- · Rollforms all standard metals with minimal or no adjustment
- Free-floating forming rollers produce less pressure and allow for more product uniformity

ELECTRICAL AND CONTROL SYSTEM

- Push button control safety wiring
- Entrance and exit control selector switch jog run
- 3/4 HP, 110 Volt, Single Phase Motor, 13.6 Ampere

STRUCTURAL STEEL FRAME

• Welded steel frame



