

SENOX<sup>®</sup>



# BARRACUDA<sup>®</sup>

Standard K-Style Gutter<sup>™</sup>



*Pictured Turnstile Upright,  
Spool and Other Optional  
Accessories Available*

*Handheld Control*



*Right / Left  
Side Mount*



*Top  
Mount*

## Full Size 7" K-Style

### Backed by the best service in the industry



Serving the Seamless Gutter Industry Since 1972

Warranty:  
3 Year Parts & Labor  
1 Year Electrical

Ph: 866-522-1696

Fax: 800-295-2702

[www.senox.com](http://www.senox.com)

# Specifications

## Dimensions

Length - 149"  
Height - 48"  
Width - 24"

## Weight

Approximately 1,490 lbs

## Drive

Powered polyurethane drive rollers  
via chains and sprockets

## Speed

Approximately 35 feet per minute

## Controls

Push button entry and exit end controls  
with "jog" feature, dongle

## Recommended Materials

18" wide  
Aluminum .027/.032  
Galvalume 26 ga.  
Copper 16 oz. 3/4 hard

## Options

- Full Coil Cradle
- Turnstile Upright
- Spool
- Front Pull Guillotine
- Standard Run Out Stand
- Machine Stand
- Transfer Bars, Set of 2

## Options



## POLYURETHANE DRIVE TRAIN

- Eliminates the need to load coil prior to transportation (less material waste)
- Eliminates slippage from cold weather and condensation

## .002 HARD CHROME PLATED STEEL FORMING ROLLERS

- Rollforms all standard metals with minimal or no adjustment
- Free-floating forming rollers produce less pressure and allow for more product uniformity

## ELECTRICAL AND CONTROL SYSTEM

- Push button control safety wiring
- Entrance and exit control selector switch jog run
- 3/4 HP, 110 Volt, Single Phase Motor, 13.6 Ampere

## STRUCTURAL STEEL FRAME

- Welded steel frame



Serving the Seamless Gutter Industry Since 1972

