Eave N Flow 5" + 6" K-Style

Part of the

Black MAX

Disappearing Accessories

Product Line



Works with any roof pitch and type.

Self cleaning ridges promote air flow, dry debris blows off system with slight breeze.

All aluminum construction prevents warping and deterioration over time.

Invisible from the ground and does not interfere with the roof.

Attached to the front and back of the gutter which strengthens the entire gutter system making it strong enough to handle snow and ice buildup and keeps pests from entering the gutter.



REMOVE AND INSTALL FOR MAINTENANCE AS NEEDED


Clean and flush existing gutters and downspouts thoroughly with water prior to installing gutter guard.

1. Position panel over gutter, rest the back of the panel against the drip edge/fascia board. Snap the front edge of the panel into the front of the gutter. Make sure all panels are level.





2. Screw front edge of panel to top of gutter lip using pre-set fastening points. Take care not to over-tighten the screw.









4. Outside Corners - Cut first panel on 45 angle. Cut second on 45 angle, leaving a slight overlap through which you can secure mitered panels together.







Gutter Guard is an integral part of a well functioning Rain Water Collection system.

KEEPS DEBRIS OUT SO SYSTEM WORKS PROPERLY



- Keeps water out of storm drains and combined sewer systems
- Controls moisture levels around the foundation of your home or property
- · Provides oxygenated, un-chlorinated water to plants and flower beds
- · Directs overflow to where you want it to be
- · Reduces water and wastewater bills
- · Conserves water in the summer months when demand is the highest

Go Green at www.senox.com